




Button Nozzle, Dual 30°, .024 Orifice

Domed button nozzle with 2 orifices, 30 degrees apart, .024 in orifice. Fits all H200 modules.




Button body, typical. Orifice layout varies by pattern.

Specifications

Nozzle type	Button (domed)
Pattern	Dual 30°
Orifices	2 orifices, 30 degrees apart
Stream angles	±15° from the centerline
Orifice diameter	.024 in
Orifice tolerance	±.0005 in
Material	Phosphor brass
Fits	All H200 modules
Store SKU	T2C80B6S

Spray pattern



Dual 30°, side view shooting down, drawn to the chart angles.

Cross references

Replaces Nordson®	238026
Graco InvisiPac	130503

About button nozzles

- Button nozzles are one piece, precision drilled brass with no insert.
- Precision drilled holes shoot straighter.

Where the beads land

Stream	0.5 in 12.7 mm	1 in 25.4 mm	1.5 in 38.1 mm	2 in 50.8 mm	2.5 in 63.5 mm	3 in 76.2 mm
15° each side	0.16 4.1	0.29 7.5	0.43 10.9	0.56 14.3	0.70 17.7	0.83 21.1

Product distance from the tip across the top. Offset from the nozzle centerline, inches in bold, millimeters in gray. Approximate: pressure, temperature, viscosity and line speed move the bead.

