




Button Nozzle, Single 45°, .010 Orifice

Domed button nozzle with 1 orifice, 45 degrees off center, .010 in orifice. Fits all H200 modules.




Button body, typical. Orifice layout varies by pattern.

Specifications

Nozzle type	Button (domed)
Pattern	Single 45°
Orifices	1 orifice, 45 degrees off center
Stream angles	45° from the centerline
Orifice diameter	.010 in
Orifice tolerance	±.0005 in
Material	Phosphor brass
Fits	All H200 modules
Store SKU	T7P34H4S

Spray pattern



Single 45°, side view shooting down, drawn to the chart angles.

Cross references

Replaces Nordson®	703464
Graco InvisiPac	130814

About button nozzles

- Button nozzles are one piece, precision drilled brass with no insert.
- Precision drilled holes shoot straighter.

Where the beads land

Stream	0.5 in 12.7 mm	1 in 25.4 mm	1.5 in 38.1 mm	2 in 50.8 mm	2.5 in 63.5 mm	3 in 76.2 mm
45°	0.60	1.10	1.60	2.10	2.60	3.10
one side	15.2	27.9	40.6	53.3	66.0	78.7

Product distance from the tip across the top. Offset from the nozzle centerline, inches in bold, millimeters in gray. Approximate: pressure, temperature, viscosity and line speed move the bead.

